

Guides									
Products	CL/CLB/CLC	VL/VLB	CM	VM	CW/CWB	VW/VWB	CSB/CSC	VS	VSC
Shore Hardness	80A	80A	90A	90A	40D	40D	65A	65A	
Color	Brown/Clear/Blue	Brown/Blue	Red	Red	White/Blue	White/Blue	Blue/Clear	Blue/Clear	
Cogged	Yes	No	Yes	No	Yes	No	Yes	No	
FDA	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Size (mm)		Add To Minimum Pulley Diameter (inch)							
Width	Height								
6	4	NR	1	NR	NR	NR	NR	NR	9/16
8	5.20	NR	1 9/16	NR	2 1/2	NR	NR	NR	1
10	6	1 3/8	1 3/4	2	2 9/16	2 3/16	2 3/4	7/8	1 3/16
13	8	1 9/16	2	2 1/2	3 3/8	2 1/2	3 1/4	1 1/8	1 3/8
17	11.50	2 1/2	3	3 3/8	4 3/4	3 3/8	4 1/4	1 9/16	2
20	12.50	NR	3 3/8	NR	5	NR	NR	NR	NR
22	14.50	3	4	4 1/4	5 1/2	4 1/4	6	NR	2 9/16

Special Profiles**									
Products	SPN - 1000	SPY - 1000	SLW 3/4	SM - 1400	TO - 9.5	TO 1/2	TO 9/16	SO 3/4	UO - 9.5
Illustration									
Hardness	88A	86A	80A	90A	83A	83A	83A	83A	83A
Size (mm)	Top Width	15.70	15.60	19.30	30	9.50	12.70	14.30	19.20
	Height	13.60	14.50	5.50	12	3.80	5.50	6.50	5.50
	Bottom Width			8		3.10	8.35	9.50	8
MPD (inch)	NR	NR	1 1/16	1	1 3/16	1 1/2	2 3/4	1 3/8	2

Products	SH - 1200	TEMB - 25	TEMW - 25	TLB - 10	TLB - 15	TLW - 30	SLC - 2300	SLC - 2104
Illustration								
Hardness	100A	95A	95A	80A	80A	80A	80A	80A
Size (mm)	Top Width	17	25	25	10	15	30	30
	Height	11.50	2	2	3.80	5	17	17
	Bottom Width		4.50	4.50	3.10	6.50	22	22
MPD (inch)	9	2 1/2	2 1/2	2	1 3/16	5	4*	3

Products	Illustration	Hardness	Size (mm)		Minimum Pulley Diameter (inch)
			Width	Height	
SH - 1300		100A/55D	16	1.70	2
SH - 1301			18	1.70	2
SH - 1302			20	1.70	2
SH - 1305			25	1.70	2
SH - 1306			14	1.70	2
SH - 1310			16	2	2 1/2
SH - 1311			18	2	2 1/2
SH - 1312			20	2	2 1/2
SH - 1313			8	2	2 1/2
SH - 1314			8	3	3 1/4
SH - 1320			10	4	4
SH - 1325			17	1.50	1 3/4

Notes: \*TLW/30 - Cogged. \*\*Special Profiles - sizes are in millimeters.

Food Approved Soft Material					
Products	Color	Hardness	Temperature Range	CoF (Steel)	FDA
Round Profiles	TB	72A	-40° C to +40° C	0.85	Yes
'V' Profiles	Transparent Blue		-40° F to +105° F		



Belt Coating Materials for the Food Industry							
Products	GIB*	MIB*	FEIB*	WIB*	FEMB-SP	FEMW-SP	FELB-SP
Illustration							
Description	Super Grip	Multi Grip	High Grip	Wood Grip	Spikes	Spikes	Spikes
Hardness	62A	62A	62A	62A	95A	95A	85A
Size	Width* (inch)	2	2	60	2 3/4	60	60
	Thickness (mm)	4	6	4	4	2/ 2.5/ 3	2/ 2.5/ 3
CoF (Steel)	0.98	1.08	0.95	1.05	0.25	0.25	0.45
Temp. Range	-5° F to +105° F			-20° F to +140° F		-40° F to +120° F	


Notes: \*For Dry Applications Only.

Belt Coating Materials								
Products	GST - 4	MST - 6	FEST	FSTF	FSTF - ST	FSTF - ST Strips	FSTF - STX Strips	GWG - 4
Illustration								
Description	Super Grip	Multi Grip	High Grip	Foam**	Foam & High Grip Top	Foam & High Grip Strips	Foam & High Grip Double Strips	Wood Grip
Hardness	65A	65A	65A	65A	65A	65A	65A	65A
Size	Width* (inch)	2	2	60	5 1/2	6	6 1/4	2 1/2
	Thickness (mm)	4	6	2, 3, 4, 5	14	6-12	4	4
CoF (Steel)	0.85	0.88	1.10	0.90	0.90	0.90/1.10	0.90/1.10	0.77
Temp. Range	-40° F to 130° F							

Notes: Width\* - Maximum available width. \*\*Foam - Made from 65A shore material, actual hardness is lower.



# Conveying Solutions 'V' & Round Profiles



www.voltabelting.com

**Corporate Headquarters Sales and Manufacturing**  
 sales@voltabelting.com

**USA**  
 Tel: +1 973 276 7905  
 Fax: +1 973 276 7908  
 Toll Free: 1-877-VOLTAUS

**EUROPE**  
 Tel: +31-546-580166  
 Fax: +31-546-579508

www.voltabelting.com

Volta Belting makes no warranty with respect to any of its products for a particular purpose. See Volta General Terms and Conditions.  
 Copyright©2011 Volta Belting Technology Ltd. CAT503EN00 - Ver. A - September 2011

The Next Step in Belting



Main table for Round profiles with columns: Round, RL, RLC, RLB, RLW, RO, ROS, RPZ, RPZS, RPN, RPS, RPB, RPBS, RM, RMS, RMDS\*, RMBS, RMW, RMWN, RH, RHN, RCW\*. Includes sub-tables for Hardness, Temp. Range, CoF (Steel), FDA/USDA, Diameter, and Hollow connectors.

Table for V-Profiles with columns: VFC, VL, VLC, VLB, VLW, VO, VO-GT\*\*, VOS\*\*, VPZ, VPZS, VPY, VPYS, VPN, VPNS, VPF, VPFS, VMF, VM, VMS, VMW\*\*, VMW-NK\*\*, VH, VHB. Includes sub-tables for Hardness, Temp. Range, CoF (Steel), FDA/USDA, Size (mm), and Inch Size.

Table for Ridge-Top and Y-Top profiles with columns: VL-RT, VLC-RT, VLW-RT, VMP-RT, VPZ-RT, VPZS-RT, VPY-RT, VPYS-RT, VPN-RT, VPNS-RT, VPF-RT, VPFS-RT, VM-RT, YMP, YPZ, YPN, YPF, YMF, Double-V, DVL, DVLW, DVO, DVOS, DVM. Includes sub-tables for Hardness, Temp. Range, CoF (Steel), FDA/USDA, Size (mm), and Inch Size.

Index: MPD - Minimum Pulley Diameter - Measurements for butt welding. In case of overlap welding please check the MPD with your local distributor. Notes: \*RMBS & RMDS - Diameter 10.5mm. \*RMDS - High UV Resistance \*\*VO-GT, VOS - Inch sizes only. Notes: \*RCW - also available with Steel, Stainless Steel & Kevlar (Aramid) reinforcement. \*\*VMW - Cogged. \*\*VMW - NK - Not Cogged.